



Comfort Roll N33.



relief of pressure points + easy lying down and rising + high lying comfort + longer lying bouts + more rumination + higher milk production



100 % new tire compound



Top surface
Hammered profile



Bottom surface.
Different height studs
with 12 mm and 20 mm



Cross section.

Comfort ●●●●○

Application	Lying surface for elevated cubicles for dairy cattle / replacement heifers
Suitability	New construction and retrofitting
Thickness	Cover sheet 13 mm Studs 20 mm Total 33 mm
Length	10 to 40 m
Width	1900 mm
Slope	With slight slope at the head and foot area on the outer 300 mm
Top surface	Hammered profile
Center	Fabric reinforcement
Bottom surface	12 mm and 20 mm studs
Penetration depth	16,1 mm according to DLG test method
Special features	+ Slope on both sides. + Full rubber profile. + Easy installation.
Installation	Yard ware
Warranty	10 years

**DIN-3763
class 3**

Advantages at a glance.

- + **Fast drainage of liquids** due to a slope on both sides.
- + **Years of dimensional stability** due to solid rubber profile.
- + **Optimum comfort** due to special stud geometry.

Special advantages of roll material.

- + **Easy cleaning** of cow paddocks due to proven surface.
- + **No joints** - less wear and dirt.
- + **Very easy to lay** with the help of roll material.
- + **Suitable for any cubicle width**, as no joints are necessary with roll material.



Specially designed stud geometry.

The comfort covering N33 is characterized by studs of different heights on the underside. This special stud geometry provides even more comfort for the cow through its cushioning function.



Fluid drainage.

Due to a slope on both sides in the head and foot area on the outer 300 mm, liquids run off faster.

Tested for you.



**HUBER TECHNIK VERTRIEBS GMBH
KOMFORTBELAG N 33**
✓ Verformbarkeit/Elastizität
✓ Dauertrittbelastung
DLG-Prüfbericht 6387

In DLG test 6386 and 6387, the deformability and elasticity of the comfort roll N33 was rated "very good".



**HUBER TECHNIK VERTRIEBS GMBH
KOMFORTBELAG N 33**
✓ BTS Rindvieh (weibliche Tiere)
DLG-Prüfbericht 6386

"BTS cattle" includes joint bonitization and behavioral observation, as well as measurement of deformability. The N33 comfort surface meets all the requirements of the DLG test.



**CONTINUOUS
MONITORING**
**RUBBER FLOOR MATS
FOR ANIMAL HOUSES**
✓ PAH harmless
✓ Manufacturing
process certification
DLG Certificate 6910

Our rubber coverings have passed the PAH test. All rubber compounds produced are below the DLG guideline values.



The installation instructions and the DLG test report on the comfort roll N33 can be found at:
www.cow-comfort-huber.com



Huber knows what cows like.



Get to know our rubber production.
Activate mobile phone camera, scan code.

Huber Technik

Stands for almost 100 years of company tradition in rubber processing.



Made in Germany.

Our family-owned company manufactures exclusively at the plant in Erding. Product development is also carried out in cooperation with our worldwide dealer network at the Upper Bavarian site.



Expert for rolled products.

Rubber floorings from Huber are supplied in roll form. This allows us to deliver our products in one piece up to a length of 100 meters. For the farmer, this means simple installation: Lay down the roll, unroll it and fasten it. On the other hand, Huber's stable floors have no joints like individual mats and therefore less possibility of wear and soiling.



What is rubber?

In addition to natural rubber, many synthetic plastics that have elastic properties are called rubber today. Rubber is originally a tough, sticky mass that bonds very well. This bonding takes place under heat and high pressure. In the process, rubber takes on the desired and final shape. This cross-linking, which is typical of rubber, is called vulcanisation. It can only take place once and cannot be reversed.




100 % unvulcanized rubber.

For rubber, the one-time vulcanisation means that it cannot be melted down again and pressed anew, but can only be crushed mechanically with a high expenditure of energy. For this reason, we only process and vulcanise new rubber and no old tyre granulate. Granulates have only little binding power of their own. In order to reshape them anyway, binders have to be used. That is why recycled products made from rubber granulate need a certain minimum strength. Our products consist exclusively of new, unvulcanised tyre compounds. This selected raw material contains high-quality components which, among other things, provide ageing resistance and ozone protection. This enables us to give a 10-year guarantee on all our products.



Elastic and durable coverings.

For the desired softness and elasticity, it is not the thickness but the quality of the material that is decisive. The new rubber we use is more elastic than recycled rubber. With less overall thickness, better resilience is achieved with unsurpassed durability. Thick mats do not usually retain their original strength and shape because they do not have the permanent elasticity of virgin rubber.



Wear-resistant rubber mats.

To determine the wear resistance of rubber products, mainly tear strength, elongation at break and abrasion are examined. In these criteria, new rubber is clearly superior to recycled rubber. That is why we can offer a minimum 10-year guarantee.



Stable floor coverings according to DIN standards.

We produce all our walking and lying surfaces according to the DIN-3763 standard. DIN-3763 standard, which sets standards for resilient barn flooring to ensure the best for animal welfare. External quality control has always been part of our development and production philosophy, so Huber's rubber floorings achieve very good values according to all DLG tests.



Our rubber mats have passed the PAH test.

PAHs are polycyclic aromatic hydrocarbons that have been proven to be carcinogenic. PAH compounds are caused by incomplete combustion processes of organic material. Accordingly, PAHs are omnipresent in our environment and also play a role in rubber floor coverings. Our stable floor coverings have been tested for PAH by the DLG (German Agricultural Association) and are found to bear no risk due to PAH when used for animal husbandry. All rubber mixtures produced are far below the DLG guideline values. The decisive factor is whether the PAHs can be absorbed into the body through the skin. Accordingly, there is no transfer of PAHs into the milk or blood of the cattle.

For more information, please visit:
www.cow-comfort-huber.com

Follow us on

You can reach us here:

Huber Technik Vertriebs GmbH
Robert-Bosch-Straße 8, 85435 Erding
+49 8122 869 122 vertrieb@huber-technik.de
www.cow-comfort-huber.com