



SCRUBBING OPTION FOR BULLS AND CATTLE

HT MOO-MASSAGE



EASY INSTALLATION

- ✓ Low expenditure of time & personnel
- ✓ Assembly time approx. 15 min.
- ✓ No special fixings or tools necessary

MAXIMUM SAFETY

- ✓ Inclined console sides prevent blunt trauma -> dissipate impacts
- ✓ Closed, stable construction without contact surfaces
- ✓ No risk of injury
Prevention of abrasions or pinching



PAH test passed

Animal welfare

Application area	Free barn, box	
Suitability	Bulls and cattle	
Substructure	Sturdy bracket made from galvanised black sheet metal	
Depth	100 mm + up to 34 mm thick rubber mat	
Dimensions	Studded mat	Console
Length	900 mm	1100 mm
Width	300 mm	560 mm
Rubber mat	20 mm thick studs	
Installation	Space-saving on stable walls	

ANIMAL WELFARE IN THE FOCUS

- ✓ Promotes the comfort behavior of the animals
- ✓ Body parts that are difficult to reach, such as flanks can be groomed with sufficient wall clearance (approx. 10 cm) and immovable resistance
- ✓ Enables vigorous scrubbing typical of the species - better blood circulation in the deeper layers of the skin and upper muscle layers

IN CONSIDERATION

- ✓ Very robust and durable
Significantly less wear and tear than brushes
Robust construction = particularly suitable for heavy use by fattening and breeding bulls
- ✓ Cost-saving HT easy-change system
Studded mats can be reordered individually and changed quickly without dismantling the bracket
- ✓ Strong, positive efficiency thanks to 20 mm studs in contrast to almost ineffective checker plate

Installation instructions and
DLG test reports can be found at:

 www.cow-comfort-huber.com



HUBER KNOWS WHAT COWS LIKE.

CUBICLE ■ ALLEY WAY ■ MILKING PARLOUR



**HUBER
TECHNIK**
Vertriebs GmbH



Get to know our
rubber production



HUBER TECHNIK STANDS FOR ALMOST 100 YEARS OF COMPANY TRADITION IN RUBBER PROCESSING.

D MADE IN GERMANY

Our family-run company manufactures exclusively at its plant in Erding. Product development is also carried out in cooperation with our global dealer network at the Upper Bavarian location.



EXPERT FOR ROLLS

Rubber flooring from Huber is supplied in rolls. This means we can supply our products seamlessly in one piece up to a length of 100 metres. For the farmer, this means simple installation: Simply lay down the roll, unroll and screw tight. On the other hand, Huber stable floor coverings have no joints as with individual mats and therefore less potential for wear and soiling.



WHAT ACTUALLY IS RUBBER?

In addition to natural rubber, many synthetic plastics with elastic properties are referred to as rubber today. Rubber is originally a tough, sticky mass that bonds very well. This bonding takes place under heat and high pressure. This gives rubber its desired and final shape. This rubber-typical cross-linking is called vulcanisation. It can only take place once and cannot be reversed.

100%

100 % VIRGIN RUBBER

The one-off vulcanisation of rubber means that it cannot be melted down and pressed again, but can only be crushed mechanically with a high energy input. For this reason, we only process and vulcanise new rubber and not used tyre granulate. Granules only have a low binding force of their own. Binding agents must be used in order to remould them. This is why recycled products made from rubber granulate require a certain minimum thickness. Our products consist exclusively of new, unvulcanised tyre compounds. This selected raw material contains high-quality components that ensure, among other things, resistance to ageing and ozone protection. This enables us to offer a 10-year guarantee on all our products.



ELASTIC AND DURABLE COVERINGS

It is not the thickness but the quality of the material that is decisive for the desired softness and elasticity. The new rubber we use is more elastic than recycled rubber. With a lower overall thickness, better resilience is achieved with unrivalled durability. Thick mats generally do not retain their original strength and shape because they do not have the permanent elasticity of virgin rubber.



WEAR-RESISTANT RUBBER COVERINGS

To determine the wear resistance of rubber products, the main criteria analysed are tensile strength, elongation at break and abrasion. In these criteria, new rubber is clearly superior to recycled rubber. This is why we can offer a minimum 10-year guarantee.



STABLE FLOOR COVERINGS ACCORDING TO DIN-STANDARDS

We produce all our walking and lying surface coverings in accordance with the DIN3763 standard. The standard sets standards for resilient stable floor coverings to ensure the best for animal welfare. External quality control has always been part of our development and production philosophy, which is why Huber rubber flooring achieves very good results in all DLG (German Agricultural Society) tests.



OUR RUBBER FLOORING HAS PASSED THE PAH-TEST

PAHs are polycyclic aromatic hydrocarbons that have been proven to be carcinogenic. PAH compounds are caused by incomplete combustion processes of organic material. Accordingly, PAHs are omnipresent in our environment and also play a role in rubber floor coverings. Our stable floor coverings have been tested for PAHs by the DLG (German Agricultural Society) and classified as PAH harmless for animal husbandry. All rubber compounds produced are well below the DLG guideline values. The decisive factor is whether the PAHs can be absorbed into the body via the skin. This means that PAHs do not pass into the milk or blood of cattle.

Follow us on

www.cow-comfort-huber.com

Huber Technik Vertriebs GmbH

△ Robert-Bosch-Str. 8 · 85435 Erding · GERMANY
☎ +49 8122 869 122 · ✉ vertrieb@huber-technik.de